

certificate ID  
**2KD71**

# HB701 Certificate of Compliance



C-100279-001

issue date 10/8/22 2:50 PM

This Product Has Been Tested and Meets the Quality Assurance Requirements of the State of Montana

Stillwater Laboratories

15275  
order

**Incoming Inspection** MSP-7.5.1.2

**Potency** MSP-7.5.1.4

LOD LOQ error

DESCRIPTION: Trimmed bud sample (1.10g) received 10/5/2022 2:45:45 PM in a marked 50mL Falcon tube, collected at dispensary/grow. 1 and sample tag B2NGO.



SECURITY FEATURE: WATERMARK MUST MATCH CERTIFICATE ID AND ISSUE DATE

### Pass / Fail Criteria

**Microbial** MSP-7.5.1.10b  
not required / not requested

**Pesticides** MSP-7.5.1.8  
not required / not requested

**Solvents** MSP-7.5.1.7  
not required / not requested

**Mycotoxins** MSP-7.5.1.8  
not required / not requested

**Moisture** MSP-7.5.1.3  
not required / not requested

**Metals** MSP-7.5.1.7  
FAIL: no failures  
PASS: Arsenic, Cadmium, Lead, Mercury

Certified by:



https://customer.a2la.org/index.cfm?event=directory\_detail&labPID=423635B2-5128-4C6F-871A-419DCF43B0D7

**Stillwater Laboratories Inc.**  
MT License L100060-002  
6073 US93N Suite 5, Olney MT 59927  
Ph 406-881-2019. www.stwlab.com

**These results are only valid for the samples tested.** • Potency (cannabinoid concentration) is calculated as: [cannabinoid] = [cannabinoid]<sub>HPLC</sub> x volume<sub>dilution</sub> / m<sub>dry</sub>. •• Decarboxyted cannabinoid concentration is calculated XXX<sub>total</sub> = 0.877 x XXX<sub>a</sub> + XXX ••• Standards are used to calibrate the resulting data and estimate error using a standard estimate of error method; LOD is the limit of detection (3.3s), LOQ is the limit of quantification (3xLOD), and experimental error is calculated from weighing, dilution, and interpolation error using the formula  $s_g^2 = \sum (\partial f / \partial i)^2 s_i^2$  where i is the contributor to error. The 95% confidence range is calculated from: (concentration) ± t<sub>CL90</sub> x s<sub>g</sub>. Sampling error is not considered in error calculations. ND = not detected (< LOD), NT = not tested, NL = no limit, NA = not applicable. ‡ = decarbed, \* = analyte is off-scope.

certificate ID  
**2KD71**



# ANALYTICAL DATA

Stillwater  
Laboratories

Report Version: 1  
Analysis Location: L-100060-

order 15275  
rec'd date 10/5/2022 2:45:45 PM  
issue date 10/8/2022 2:50:47 PM  
order 15275

## Methods and Instruments

MSP-7.3.1.1	BAL-05	10/5/2022	MSP-7.5.1.7	QP2020/HS20	10/6/2022
MSP-7.5.1.2	YSC HD801m12	10/6/2022	MSP-7.5.1.8	LCMS8060	10/6/2022
MSP-7.5.1.3	6MOC63u	10/6/2022	MSP-7.5.1.8	LCMS8060	10/6/2022
MSP-7.5.1.4	LC-2030C	10/6/2022	MSP-7.5.1.10b	Hardy Diag	10/6/2022
MSP-7.5.1.6	QP2020/HS20	10/6/2022	MSP-7.5.1.11	ICPMS2030	10/6/2022 L-100060-002

SECURITY FEATURE: WATERMARK MUST MATCH CERTIFICATE ID AND ISSUE DATE

## Metals

	MSP-7.5.1.7	limit	LOD	LOQ	error	result
Arsenic	99 ppb	10000 ppb	8.1	24.3	±25.9 ppb	PASS
Cadmium	ND	4100 ppb	8.7	26.1	±26.1 ppb	PASS
Lead	ND	6000 ppb	13.6	40.7	±40.7 ppb	PASS
Mercury	ND	2000 ppb	6.8	20.5	±20.5 ppb	PASS

**These results are only valid for the samples tested.** • Standards are used to calibrate the resulting data and estimate error using a standard estimate of error method; LOD is the limit of detection (3.3s), LOQ is the limit of quantification (3xLOD), and experimental error is calculated from weighing, dilution, and interpolation error using the formula  $s_g^2 = \sum (\partial f / \partial i)^2 s_i^2$  where i is the contributor to error. The 95% confidence range is calculated from: (concentration) ±  $t_{CL90} \times s_g$ . Sampling error is not considered in error calculations. ND = not detected (< LOD), NT = not tested, NL = no limit, NA = not applicable.

Certified by:



**Stillwater Laboratories Inc.**  
MT License L0001, L0007, L0010  
6073 US93N Suite 5, Olney MT 59927  
1408 Unit 4 Gold Ave, Bozeman MT 59715  
Ph 406-881-2019. www.stwlab.com